



System Fact Sheet

SYSTEM

Introduced: April 1997
Discontinued: n/a
Gestalt ID: 515
Form Factor: PM 4400
Weight (lbs.): 24
Dimensions (inches): 5.43 H x 15.12 W x 17.37 D

POWER

Max. Watts: 150
Amps: 3.00
BTU Per Hour: 513
Voltage Range: 110/220
Freq'y Range (Hz): 47-63
Battery Type: 4.5V alkaline
 Soft Power
 Monitor Power Outlet

PORTS

ADB: 1
Video: DB-15
Floppy: none
SCSI: DB-25
GeoPort Connectors: 2
Ethernet: 10baseT
Microphone Port Type: PlainTalk
 Printer **Speaker**
 Modem **Headphone**
 Remote Control
Includes PC game port on PC Compatibility card.

VIDEO

Built-in Display: none

Maximum Color Bit-depth¹ At:

VRAM Speed:	VRAM Needed:	Video Configuration:	512 x384	640 x400	640 x480	640 x870 ²	800 x600	832 x624	1024 x768	1152 x870	1280 x1024
n/a	1x2MB	2MB EDO DRAM	24	n/a	24	8	24	16	16	16	8
	1x4MB	4MB SGRAM	24	n/a	24	8	24	24	24	16	16

¹ 1-bit = Black & White; 2-bit = 4 colors; 4-bit = 16 colors; 8-bit = 256 colors; 16-bit = Thousands; 24-bit = Millions

² The maximum color depth listed for 640x870 is 8-bit, reflecting the capabilities of the Apple 15" Portrait Display.

LOGIC BOARD

Main Processor: 603e, 200 MHz
PMMU: integrated
FPU: integrated
Data Path: 64-bit, 40 MHz
L1 Cache: 32K
L2 Cache: 256K
Secondary Processor: Cyrix P166 6x86
Slots: 2 PCI, comm II

Supports one 7-inch and one 12-inch PCI slot. The 12-inch PCI slot is occupied by the PC Compatibility card.

MEMORY

Memory on Logic Board: none
Minimum RAM: 32MB
Maximum RAM: 160MB
RAM Slots: 3 168-pin
Minimum RAM Speed: 60 ns
RAM Sizes: 8, 16, 32, 64MB
Install in Groups of: 1

Uses JEDEC-standard 3.3-volt unbuffered EDO DIMM devices. DRAM slot 1 supports only single-bank DIMMs.

SOFTWARE

Speech Recognition Supported

Addressing Modes: 32-bit
Original SSW: 7.5.3
Original Enabler: System Enabler 827

ROM ID: \$077D
ROM Version: \$3A
ROM Size: 4MB
AppleTalk Version: 60.1.1

Supported Macintosh System Software:

- <1.0 6.0 6.0.8 7.1P2 7.1.2
- 1.0 6.0.1 7.0 7.1P3 7.5
- 1.1 6.0.2 7.0.1 7.1P5 7.5.1
- 2.0 6.0.3 7.0.1P 7.1P6 7.5.2
- 2.0.1 6.0.4 7.1 7.1.1 (Pro) 7.5.3
- 5.0 6.0.5 7.1P 7.1.1 7.5.5
- 5.1 6.0.7 7.1P1 7.1.2 7.6

Includes Windows 95 for use with PC Compatibility card.

SOUND

Microphone Port Type: PlainTalk
 Built-in Microphone
Sound In: stereo, 16-bit
Sound Out: stereo, 16-bit

STORAGE

Supports Internal CD-ROM

Floppy Size: 1.44MB
Floppy Inject: manual
Internal HD Size: 2GB
Internal HD Interface: ATA
Original CD-ROM Speed: 12x